

2. Features & Specifications

(1) Features

- Consists of one internal 10Mbps Ethernet segment and one internal 100Mbps Fast Ethernet segment.
- Supports five Auto-Negotiation RJ45 ports which automatically sense and select optimum speed and route data traffic to corresponding internal segments.
- Built-in Uplink port with the first port to connect with regular straight-through cable to another hub.
- Built-in internal switching function automatically switches data traffic between devices running at different speed, establishes communications between ports running at 10Mbps and 100Mbps.
- Provides one Extension port (the 1th port) that can be linked to another Fast Ethernet hub or Ethernet Hub (10Mbps) up to 100 meters.
- Desktop size and wall mountable
- Two-year warranty

(2) Specifications

- Standards : IEEE 802.3 & 802.3u
- 10/100Mbps Ports : RJ45 x 5
- Hub LEDs : Power, 10/100, 10M Collision, 100M Collision
- Port LEDs : 100Mbps, Link/Activity
- Dimensions : 7.4 x 3.9 x 1.0 in. / 187 x 99 x 26 mm (Plastic Case)
- Weight : 0.77 lb./350g (Plastic Case),
- Power : External full range power adapter
- Operating Temperature : 32-131°F (0-55°C)
- Operating Humidity : 10-95% (Noncondensing)
- Emission : FCC Class B & CE

2. Features & Specifications

(1) Features

- Consists of one internal 10Mbps Ethernet segment and one internal 100Mbps Fast Ethernet segment.
- Supports five Auto-Negotiation RJ45 ports which automatically sense and select optimum speed and route data traffic to corresponding internal segments.
- Built-in Uplink port with the first port to connect with regular straight-through cable to another hub.
- Built-in internal switching function automatically switches data traffic between devices running at different speed, establishes communications between ports running at 10Mbps and 100Mbps.
- Provides one Extension port (the 1th port) that can be linked to another Fast Ethernet hub or Ethernet Hub (10Mbps) up to 100 meters.
- Desktop size and wall mountable
- Two-year warranty

(2) Specifications

- Standards : IEEE 802.3 & 802.3u
- 10/100Mbps Ports : RJ45 x 5
- Hub LEDs : Power, 10/100, 10M Collision, 100M Collision
- Port LEDs : 100Mbps, Link/Activity
- Dimensions : 7.4 x 3.9 x 1.0 in. / 187 x 99 x 26 mm (Plastic Case)
- Weight : 0.77 lb./350g (Plastic Case),
- Power : External full range power adapter
- Operating Temperature : 32-131°F (0-55°C)
- Operating Humidity : 10-95% (Noncondensing)
- Emission : FCC Class B & CE